

POPR™

Pop Open Pressure Relief

When the red band shows, indicates the open mode and system overpressure



No red band showing indicates the closed mode and normal operation

The CPI POPR™ is designed to replace atmospheric rupture assemblies, being automatically activated when the divider block system over pressures.

The POPR™ snaps open and diverts the oil to the lubricator reservoir, a closed container, the lubricator pump oil supply line or back to the compressor frame. The POPR™ unit remains in open position until reset with a simple snap to close action by a technician - no need to replace a ruptured disc again.

CPI POPR™ benefits and features:

- Environment - eliminates oil spills on compressor skid
- Safety - protects a technician from possible injury caused by high pressure oil squirting from a blown rupture disc
- Reliability - opens at a specific set pressure to protect compressor from damage
- Protection - remains in open position after system over pressures, until reset by a technician with a simple push on the bottom of the POPR™
- Guaranteed - works with and can be easily fitted to all divider block systems
- Solves - the problems associated with all atmospheric rupture assemblies and potential damage to a compressor

Part references:

65005000POPR35A POPR35A POPR 3500 psi (241 Bar) - W/Elbow & Fitting

65005000POPR55A POPR55A POPR 5500 psi (379 Bar) - W/Elbow & Fitting

Inlet Thread: 1/8" NPT (Male)

Outlet Thread: 1/16" NPT (Female)

